

# IN VITRO SIMULATION OF GASES PRODUCTION BY LIVESTOCK EFFLUENT USING MICRO GC FUSION®




Joguet N<sup>1</sup>, Morin-Ogier Q<sup>1</sup>, Jing L<sup>2</sup>, Jamois F<sup>2</sup>, Ibrahima H<sup>3</sup>.  
 1 Pôle Environnement et Effluent, Centre Mondial de l'Innovation Roullier, Saint Malo  
 2 Pôle Physico-Chimie et Bio-analyse, Centre Mondial de l'Innovation Roullier, Saint Malo  
 3 Chemlys, Vénissieux



## CONTEXT

Agriculture is responsible for 94% of ammonia emissions (NH<sub>3</sub>) in France, according to the SECTEN report in 2018. This gas, which is harmful to humans as well as animals, contributes to global climate deregulation and the creation of fine particles in the atmosphere. In addition, 68% of the methane (CH<sub>4</sub>) produced in France comes from livestock farming. Hydrogen disulfide (H<sub>2</sub>S) and nitrous oxide (N<sub>2</sub>O) are molecules that also result from agricultural activity. Livestock effluents and their management are one of the main sources of these different gases. At the laboratory level, the detection and quantification of these molecules isolated or mixed is very important to understand production mechanisms and monitoring the effects of external factors or additives.

## PRINCIPLE OF OPERATIONS



## APPLICATIONS


### Anaerobic digestion






Anaerobic digestion of organic matter produces methane (CH<sub>4</sub>) from various effluent sources. Degradation of carbonaceous matter also produces carbon dioxide (CO<sub>2</sub>) and hydrogen sulphide (H<sub>2</sub>S).

In the laboratory, anaerobic digestion reaction simulations are formulated, and the production of these different gases are monitored in real time using the µGC, allowing to obtain precise kinetics over very long periods (10 days).

H<sub>2</sub>S is a harmful and odorous compound which is also responsible for concrete corrosion in the digesters



### Results




The biogas composition obtained is consistent with the literature (about 60% CH<sub>4</sub>, 40% CO<sub>2</sub>, 0,08% H<sub>2</sub>S; O<sub>2</sub><1%). This type of analysis makes it possible to test additives allowing for example to accelerate the appearance of CH<sub>4</sub> or to reduce the production of H<sub>2</sub>S.

Module A is used to separate and quantify CH<sub>4</sub> and traces of O<sub>2</sub> and N<sub>2</sub>. Module B is used to separate and quantify H<sub>2</sub>S and CO<sub>2</sub>.

The use of the stream selector allows for the parallel analysis of 16 minitanks of anaerobic digestion and to follow the long-term kinetics of gas production.


### Aerobic degradation



The litter in breeding is a mixture of dry organic matter (straw, wood chips etc...), urine and faeces. This mixture decomposes in the presence of oxygen (composting process). Nitrogen compounds such as uric acid and urea produce ammonia (NH<sub>3</sub>) and nitrous oxide (N<sub>2</sub>O).

Ammonia is a dangerous gas that can induce severe lung infections for the animal or breeder. In addition, the loss of nitrogen as a gas decreases the fertilizer value of the effluent for the farmer's crops.



### Results



NH<sub>3</sub> is difficult to separate from water when using isocratic chromatographic separation techniques. Micro GC Fusion allows the separation and the determination of NH<sub>3</sub> and N<sub>2</sub>O molecules produced by bedding reconstituted in laboratory (excreta + urea + straw). Thanks to the Micro GC temperature ramping function, separation and resolution are better.

The simulated bedding allows to control biochemical parameters (carbon content, nitrogen content, moisture content...) and physical parameters, to have a good repeatability of gas production.

These bedding treatment test protocols will play a role in slowing down ammonia production.



## CONCLUSION

The microGC Fusion allows real-time and simultaneous analysis of the main gases from agricultural activities (CO<sub>2</sub>, CH<sub>4</sub>, NH<sub>3</sub>, N<sub>2</sub>O, H<sub>2</sub>S). Coupled with laboratory protocols, this equipment allows the establishment of kinetics of production of these gases, following different modalities. It allows us to study different models of animal litter, composting effluent or agricultural biogas production. These in vitro studies allow also rapid and accurate screening of different modalities and situations that would be impossible to quickly reconstruct on a field scale. The multi-channel technology, combined with the µGC, allows automation over the long period of gas production kinetics. These kinetics will be more or less rapid depending on the biochemical reactions considered. Simultaneous analysis of the gases allows complex monitoring of the atmospheres. For example, creation of an anaerobic atmosphere and thus follow the production of CH<sub>4</sub> and H<sub>2</sub>S resulting from it, during biogas production. The µGC is also capable of analyzing sample in gas bag, syringe or any other container thanks to its internal pump. This function is useful on field application.

Chemlys, official distributor of the analyzer in France, assists its customers with application support. This includes evolutions of the analysis solution for new processes (method setting, automation, sampling, etc.)

**Nicolas Joguet**  
 Chef de pôle Environnement et Effluent  
 nicolas.joguet@roullier.com  
 18 av. Franklin Roosevelt 35400 Saint Malo

**Lun Jing**  
 Chef de pôle Métabolomique - PCBA  
 lun.jing@roullier.com  
 18 av. Franklin Roosevelt 35400 Saint Malo

**Hassanati Ibrahima**  
 Responsable commerciale  
 h.ibrhima@chemlys.com  
 4 rue Roger Planchon, 69200 Vénissieux

**Eloïse Teboul**  
 Ingénieur d'application  
 e.teboul@chemlys.com  
 4 rue Roger Planchon, 69200 Vénissieux